RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel GmbH

28-CPR-07.2013

EN13240:2001/A2:2004/AC:2007

Notified Body:

Space heating in residential buildings without Intended use:

possible supply of hot water

ALPHA II Name:

Height		909 mm
Width		504 mm
Depth		392 mm
Fire safety		pass
Safety distance to combustible material	rear	200 mm
	sides	200 mm
	top	500 mm
	front	800 mm
	floor	0 mm
Emission of combustion products		pass
CO-Emmision at nominal heat output		< 0,12 %
CO-Emmision at nominal heat output		< 1,25 g/Nm ³
Release of dangerous substances		NPD
Surface temperature		pass
Electrical safety		pass (*)
Cleanability		pass
Durability		pass
Mechanical resistance (to carry chimney)		NPD
Maximum operating pressure		not applicable
Flue gas temperature		240,7 °C
at the measuring section at nominal heat output		
Flue gas temperature		288,8 °C
outlet at nominal heat output		
Thermal output		pass
Nominal- / part load heat output	7 kW	3,5 kW
Nominal- / part load space heat output	7 kW	3,5 kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency		pass
Nominal- / part load Efficiency	80,7 %	81,4 %
		ood logs
Suitability for installation to a shared flue system		yes
Emission (addition)	2	
CO wood logs	g/Nm ³	< 1,25
PM wood logs	g/Nm³	< 0,04
OGC wood logs	g/Nm ³	< 0,12
NO _x wood logs	g/Nm³	< 0,20
Emission (requirements according AT 15A)	1	
CO wood logs	mg/MJ	< 1100
PM wood logs	mg/MJ	< 35
OGC wood logs	mg/MJ	< 50
NO _x wood logs	mg/MJ	< 150

and using the appliance! (*) only for models with RIKATRONIC

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

ALBUL

Micheldorf, 16.12.2021

Place and date of issue