## RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel GmbH

3706-CPR-07.2013

## EN13240:2001/A2:2004/AC:2007

Notified Body: 1746

Space heating in residential buildings without Intended use:

possible supply of hot water

Name: FORMA 6 kW

Height Width Depth		1541 mm
		584 mm 584 mm
Safety distance to combustible material	rear	150 mm
	sides	150 mm
	top	500 mm
	front	800 mm
	floor	0 mm
Emission of combustion products		pass
CO-Emmision at nominal heat output		< 0,12 %
CO-Emmision at nominal heat output		< 1,25 g/Nm <sup>3</sup>
Release of dangerous substances		NPD
Surface temperature		pass
Electrical safety		pass (*)
Cleanability		pass
Durability		pass
Mechanical resistance (to carry chimney)		NPD
Maximum operating pressure		not applicable
Flue gas temperature at the measuring section at nominal heat output		233,7 °C
Flue gas temperature outlet at nominal heat output		280,4 °C
Thermal output		pass
Nominal- / part load heat output	6 kW	- kW
Nominal- / part load space heat output	6 kW	- kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency		pass
Nominal- / part load Efficiency	81,7 %	- %
recommended fuel type	wo	ood logs
Suitability for installation to a shared flue system		yes
Emission (addition)		
CO wood logs	g/Nm³	< 1,25
PM wood logs	g/Nm <sup>3</sup>	< 0,04
OGC wood logs	g/Nm³	< 0,12
NO <sub>x</sub> wood logs	g/Nm³	< 0,20
Emission (requirements according AT 15A)		
CO wood logs	mg/MJ	< 1100
PM wood logs	mg/MJ	< 35
OGC wood logs	mg/MJ	< 50
NO <sub>x</sub> wood logs	mg/MJ	< 150
Pleas read manufacturer's operating instructions carefull		

and using the appulation:
(\*) only for models with RIKATRONIC

ALBUL

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 16.12.2021

Place and date of issue