## RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel GmbH

1806-CPR-07.2013

FN1321	∩∙2∩∩1	/A2.200/	/AC:2007

Notified Body: 1746

Intended use: Space heating in residential buildings without

possible supply of hot water

FOX II 6 kW / FOX II RIKATRONIC3 6 kW Name:

Height	1039 mm	
Width	550 mm	
Depth	494 mm	
Fire safety		pass
	rear	200 mm
	sides	200 mm
Safety distance to combustible material	top	500 mm
	front	800 mm
	floor	0 mm
Emission of combustion products	pass	
CO-Emmision at nominal heat output	< 0,12 %	
CO-Emmision at nominal heat output	< 1,25 g/Nm <sup>3</sup>	
Release of dangerous substances		NPD
Surface temperature	pass	
Electrical safety		pass (*)
Cleanability	pass	
Durability	pass	
Mechanical resistance (to carry chimney)	NPD	
Maximum operating pressure	not applicable	
Flue gas temperature		242,3 °C
at the measuring section at nominal heat output		242,5 C
Flue gas temperature	290,8 °C	
outlet at nominal heat output		
Thermal output	pass	
Nominal- / part load heat output	6 kW	- kW
Nominal- / part load space heat output	6 kW	- kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency	pass	
Nominal- / part load Efficiency	82%	- %
recommended fuel type		ood logs
Suitability for installation to a shared flue system		yes
Emission (addition)		
CO wood logs	g/Nm³	< 1,25
PM wood logs	g/Nm³	< 0,04
OGC wood logs	g/Nm³	< 0,12
NO <sub>x</sub> wood logs	g/Nm³	< 0,20
Emission (requirements according AT 15A)		
CO wood logs	mg/MJ	< 1100
PM wood logs	mg/MJ	< 35
OGC wood logs	mg/MJ	< 50
	mg/MJ	< 150

and using the appliance:
(\*) only for models with RIKATRONIC

ALBUL

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 16.12.2021

Place and date of issue