RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel GmbH

15-CPR-07.2013

FN1321	∩∙2∩∩1	/A2.200/	/AC:2007

Notified Body: 1746

Intended use: Space heating in residential buildings without

possible supply of hot water

IMPOSA Name:

Height	od logs - system 3	1193 mm
Width		
		578 mm
Depth Fine cofety.	516 mm	
Fire safety		pass
	rear	200 mm
- 6	sides	200 mm
Safety distance to combustible material	top	500 mm
	front	800 mm
	floor	0 mm
Emission of combustion products		pass
CO-Emmision at nominal heat output	< 0,12 %	
CO-Emmision at nominal heat output	< 1,25 g/Nm ³	
Release of dangerous substances	NPD	
Surface temperature	pass	
Electrical safety	pass (*)	
Cleanability	pass	
Durability	pass	
Mechanical resistance (to carry chimney)	NPD	
Maximum operating pressure		not applicable
Flue gas temperature	187,7 °C	
at the measuring section at nominal heat output		
Flue gas temperature	225,2 °C	
outlet at nominal heat output Thermal output		nass
Nominal- / part load heat output	10 kW	pass
	10 kW	5 kW
Nominal / part load space heat output	10 kW	5 kW
Nominal- / part load water heat get output folder path Efficiency	not applicable	not applicable
•	000/	pass
Nominal- / part load Efficiency recommended fuel type	86%	87,4 % ood logs
Suitability for installation to a shared flue system	-	yes
Emission (addition)		yes
CO wood logs	g/Nm ³	< 1,25
PM wood logs	g/Nm³	< 0,04
OGC wood logs	g/Nm ³	< 0,12
NO _x wood logs	g/Nm³	< 0,20
Emission (requirements according AT 15A)		·
CO wood logs	mg/MJ	< 1100
PM wood logs	mg/MJ	< 35
OGC wood logs	mg/MJ	< 50

and using the appliance! (*) only for models with RIKATRONIC

SLBUL

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 16.12.2021

Place and date of issue