CE

RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel GmbH

18

4606-CPR-07.2013

EN13240:2001/A2:2004/AC:2007

Notified Body: 1746

Intended use: Space heating in residential buildings without

possible supply of hot water

Name: SWING 6 kW / SWING RIKATRONIC4 6 kW

Descriptioin: space heating appliances fired by wood logs - system 3

Descriptioin: space heating appliances fired by woo	d logs - system 3	
Height		1405/143010 mm
Width		520 mm
Depth		520 mm
Fire safety		pass
Safety distance to combustible material	rear	150 mm
	sides	150 mm
	top	500 mm
	front	800 mm
	floor	0 mm
Emission of combustion products		pass
CO-Emmision at nominal heat output		< 0,12 %
CO-Emmision at nominal heat output		< 1,25 g/Nm ³
Release of dangerous substances		NPD
Surface temperature		pass
Electrical safety		pass (*)
Cleanability		pass
Durability		pass
Mechanical resistance (to carry chimney)		NPD
Maximum operating pressure		not applicable
Flue gas temperature		215 °C
at the measuring section at nominal heat output		
Flue gas temperature		258 °C
outlet at nominal heat output		
Thermal output		pass
Nominal- / part load heat output	6 kW	- kW
Nominal- / part load space heat output	6 kW	- kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency		pass
Nominal- / part load Efficiency	83,9 %	- %
recommended fuel type	w	rood logs
Suitability for installation to a shared flue system		yes
Emission (addition)		
CO wood logs	g/Nm ³	< 1,25
PM wood logs	g/Nm ³	< 0,04
OGC wood logs	g/Nm ³	< 0,12
NO _x wood logs	g/Nm³	< 0,20
Emission (requirements according AT 15A)		
CO wood logs	mg/MJ	< 1100
PM wood logs	mg/MJ	< 35
	mg/MJ	< 50
OGC wood logs	IIIg/IVIJ	1 30

and using the appliance!
(*) only for models with RIKATRONIC

Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertal 20
Tel: +43 (07582/686-14, Fax DW: -43
www.rika.at

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 16.12.2021

Place and date of issue