

RIKA Innovative Ofentechnik GmbH A-4563 Micheldorf, Müllerviertel 20

17

0062-CPR

EN 13240:2001/A2:2004/AC:2007

Notified Body Nr.: 1746

Intended use: Space heating in residential buildings without water supply

Name: COOK space heating appliances fired by wood logs – system 3

(height x width x depth = 1030 mm x 505 mm x 435 mm)

(Holghe x Widen x dopen = 1000 him x 000 him x 400 him)				
Fire safety			pass	
Distance to combustibles		rear sides ceiling floor	100 mm 100 mm 800 mm 0 mm	
Emission of combustion products			pass	
- CO emission — wood logs 0,08% / nom			inal heat output	
Release of dangerous substances			NPD	
Surface temperature			pass	
Electrical safety			not applicable	
Cleanability			pass	
Maximum operating pressure			not applicable	
Flue gas outlet temperature at nominal heat output			286,4 °C	
Mechanical resistance (to carry a chimney)			NPD	
Thermal output / Energy efficiency			pass	
- nominal heat output			8 kW	
- water heat output			not applicable	
- space heat output			8 kW	
- efficiency			81,5 %	
recommended fuel type	woo	od logs		
Shared flue system		yes		
Emission (addition) - PM wood logs - OGC wood logs - NO _x wood logs Emission (requirements according AT 15A - CO wood logs - PM wood logs - OGC wood logs - NO _x wood logs		30,5 mg/m _N ³ 28,5 mg/m _N ³ 109 mg/m _N ³ 475,5 mg/MJ 19 mg/MJ 21,5 mg/MJ 68,5 mg/MJ		
Please read manufacturer's operating instructions carefully before installing and using the appliance!				

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 25.09.2017



