

RIKA Innovative Ofentechnik GmbH A-4563 Micheldorf, Müllerviertel 20

20

0074-CPR-07.2013

EN 14785:2006

Notified Body Nr.: 1746

Intended use: Space heating in residential buildings with possible supply of hot

Name: DOMO BACK, DOMO BACK MA

space heating appliances fired by wood pellets - system 3 (height x width x depth = 1115 mm x 793 mm x 433 mm)

(height x width x depth = 1115 mm x 793 mm x 433 mm)			
Fire safety			pass
Distance to combustibles		rear sides ceiling floor	100 mm 100 mm 800 mm 0 mm
Emission of combustion products			pass
- CO emission — wood pellets 0,006% / nor output			ninal heat
Release of dangerous substances			NPD
Surface temperature			pass
Electrical safety			pass
Cleanability			pass
Maximum operating pressure			not applicable
Flue gas outlet temperature at nominal heat output			178,1 °C
Mechanical resistance (to carry a chimney)			NPD
Thermal output / Energy efficiency			pass
- nominal heat output			10 kW
- water heat output			not applicable
- space heat output			10 kW
- efficiency			91 %
Durability pass			pass
recommended fuel type	wood	pellets	
Shared flue system		yes	
Emission (addition) - PM wood pellets - OGC wood pellets - NO _x wood pellets		10 mg/m _N ³ < 3 mg/m _N ³ 116,5 mg/m _N ³	
Emission (requirements according AT 15 - CO wood pellets - PM wood pellets - OGC wood pellets - NO _x wood pellets			50,5 mg/MJ 7 mg/MJ < 3 mg/MJ 76,5 mg/MJ
Please read manufacturer's operating instructions carefully before			

Signed on behalf of the manufacturer

installing and using the appliance!

Andreas Bloderer / product manager

Name and function Micheldorf, 07.07.2020

Place and date of issue

