



RIKA Innovative Ofentechnik GmbH

A-4563 Micheldorf, Müllerviertel 20

14

0029-CPR

EN 14785:2006

Notified Body Nr.: 1746

Intended use: Space heating in residential buildings without water supply

Name: DOMO space heating appliances fired by wood pellets – system 3
(height x width x depth = 1115 mm x 793 mm x 433 mm)

Fire safety		pass
Distance to combustibles	rear sides ceiling floor	100 mm 100 mm 800 mm 0 mm
Emission of combustion products		pass
- CO emission	- wood pellets	0,004% / nominal heat output
Release of dangerous substances		NPD
Surface temperature		pass
Electrical safety		pass
Cleanability		pass
Maximum operating pressure		not applicable
Flue gas outlet temperature at nominal heat output		135,5 °C
Mechanical resistance (to carry a chimney)		NPD
Thermal output / Energy efficiency		pass
– nominal heat output		10 kW
– water heat output		not applicable
– space heat output		10 kW
– efficiency		92,7 %
Durability		pass
recommended fuel type	wood pellets	
Shared flue system		yes
Emission (addition)		
- PM	wood pellets	18 mg/m ³
- OGC	wood pellets	< 3 mg/m ³
- NO _x	wood pellets	114,5 mg/m ³
Emission (requirements according AT 15A)		
- CO	wood pellets	29 mg/MJ
- PM	wood pellets	11 mg/MJ
- OGC	wood pellets	< 3 mg/MJ
- NO _x	wood pellets	73 mg/MJ
Please read manufacturer's operating instructions carefully before installing and using the appliance!		

Signed on behalf of

the manufacturer

Andreas Bloderer / product manager



Name and function

Micheldorf, 12.01.2016

Place and date of issue

i. A. [Signature]